







The PrintPAD MC70/75 portable thermal printer works in the most rugged environments to enable the production of hardcopy back-ups of digital information and signature printing, as well as the generation of receipts, tickets and labels for a variety of applications.

The sleek design of the PrintPAD allows users to conveniently and securely carry their mobile computer, communicate with the printer, as well as charge both the mobile computer and the printer, all in a single integrated package. This innovative one-piece printer system combines an enhanced 4" wide thermal printer, the 4te, with an embedded communications charging cradle designed for use in a number of different applications with the Motorola® MC70/75 handheld computer.

Application Functions

Beverage & Food Sales: Generate up to 2,240 - 6" (152 mm) receipts with graphics and logos.

Field Service: Print work summary reports at the point-of-service.

Route Accounting & Direct Store Delivery (DSD): Print real-time information such as inventory-level data at the customer site or in the warehouse.

Rugged Mobile Point-of-Sale (POS): Scan items, take credit card payment and issue a customer receipt anywhere on the premises (requires optional insertion magnetic stripe card reader).

Proof of Delivery: Print high-resolution signatures.

Transportation & Logistics: Print compliance shipping and inventory labels.

Law Enforcement: Generate citations or tickets at the roadside.

Designed for Comfort and Ease of Use. The PrintPAD MC70/75, with integrated carry strap, is designed for maximum user comfort. PrintPAD MC70/75 simply "wakes up" automatically when data is received so there are no buttons or switches required for operation. After printing, the unit returns to "sleep" mode to conserve battery life without any user intervention.

Mission-Critical, Global Mobility Solutions. Meet mobile application challenges with the PrintPAD MC70/75 one-piece printing solution. To ensure that the PrintPAD meets your language needs today and tomorrow, any international character set can be added.

Rugged and Reliable. With uncompromising standards, the PrintPAD MC70/75 was engineered throughout to withstand even the most punishing portable applications. It can take all the bumps and knocks inherent in the mobile workplace.

Two Year Warranty. The PrintPAD MC70/75's rocksolid print mechanism is proven to provide years of service where other printers fail. The full two year warranty, even on the printhead, offers peace of mind with our promise to stand behind every product we sell.



**Every one of the original O'Neil printers deployed six years ago is still out in the field. We've added units because we are growing, but we've never replaced any.

That's quite a testament. **

Mr. Bob Travatello
Chief Information Officer
Blue Rhino, Inc.

PrintPAD™ for Motorola® MC70/75

The PrintPAD MC70/75 is compatible with the MC70 and MC75 handheld computers from Motorola. This elegant solution includes all the standard features of a PrintPAD on a much smaller footprint. The PrintPAD MC70/75 features faster processing, a greater memory capacity, Bluetooth connectivity and DEX capabilities. It's also easier to use with an external DC jack for simultaneous charging of the printer and handheld, quick release battery clamps, and external LEDs to easily determine the printer's Bluetooth, charging and power status.



Standard Features at a Glance

- Supports all Motorola MC70 and MC75 hand-held computer models.
- Optional integrated DEX/UCS port for seamless and automatic downloads/uploads and printing.
- Advanced 32-bit architecture RISC processor, external LED status indicators, quick release battery clamps and optional Bluetooth® connectivity.
- Prints up to 2,240 6" (152 mm) receipts on a single charge.
- Includes an 80-column condensed font for invoice printing.
- Powered by two 2200 mAh-capacity Lithium-ion batteries with an external DC jack for simultaneous charging of both the printer and mobile computer.
- Automatic and user-definable settings extend battery life.
- Supports international character sets and any Bitstream® bitmap font**.

11.8" x 7.5" x 2.4" (298 x 191 x 61mm)

- Easy Print® protocol supports all popular bar codes, lines, boxes, graphics, system status, memory, formats and fonts.
- Supports the printing of 1D bar codes and 2D symbologies.

Physical Characteristics

· External Charge Contacts (E-Charge)

Optional integrated, streamlined magnetic swipe card reader.



PrintPAD™ MC70/75

Specification Highlights PrintPAD™ MC70/75 Portable Thermal Printer

Dimensions	11.8" X 7.5" X 2.4" (298 X 191 X 61MM)
Weight	printer only: 2.4 lbs (1.09 kg) with batteries, paper, and handheld: 3.8 lbs (1.72 kg)
Drop Specification	4 ft (1.2 m) (tested with terminal)
User Environment	
Operating Temperature	-4° F to 122° F (-20° C to 50° C)
Storage Temperature	-40° F to 158° F (-40° C to 70° C) (without hand-held computer)
Charging Temperature	41° F to 104° F (5° C to 40° C)
Relative Humidity	10% to 90% non-condensing
ESD Protection	8 kV Air, 4 kV contact
Communications	
Serial RS-232	460.8 kbps
Cradle	Standard MC70/75 interface connector
Bluetooth®	v1.2 (compatible with v1.1 devices)
DEX Port	DEX/UCS standard
Print Technology	
Printhead	Direct thermal, 203 dots per inch (8 dots per mm), 4.10" (104 mm) print width
Printhead Warranty	2 years*
Print Mechanism Speed	2" per second (51 mm per second)
Media	
Туре	Direct thermal receipt paper (standard, premium, heavy duty, long-life, image protect, hi-temp, and all weather), synthetic media, UV coated media, limited label support. For optimum print quality and printer performance, use Certified O'Neil supplies.
Capacity	2.25" (57 mm) maximum roll diameter (O.D.) 0.4" (10 mm) l.D. core
Width	4.41" (112 mm)
Options / Accessories	
 3" Spindle Bracket AC Adapter Cigarette Lighter Adapter Cleaning Cards & Kits DB9 F Download Cable 	 Hand Strap Magnetic Stripe Card Reader Paper Settlement Room Bracket Shoulder Strap

Spare Batteries

• Truck-Mount Brackets

_	
Battery	(2) 7.2V Lithium-ion (Li-ion), 2200 mAh (for a total of 4400 mAh)
DC Input	External DC jack, 12-15V built-in spike and surge protection
Endurance Bluetooth:	Prints approx. 6,900" or 1,150 – 6" receipts on a sing battery charge
Printer Recharging	7-9 hours from AC adapter or cigarette lighter adapte
Hand-Held Recharging	4 hours from AC adapter or cigarette lighter adapter
Fonts & Languages	
Memory Capacity	Flash/RAM Memory: 4 MBytes / 2 MBytes
Standard Fonts	5.5CPI, 7.2CPI, 10.2 CPI, 10.7CPI, 18.5CPI 20.4CPI, 22.6CPI & 34.0CPI (additional fonts available)
Optional Characters	Arabic, Asian (including Big 5, Simplified Chinese, and Shift JIS), Greek, Hebrew, OCRA, OCRB, Unicode sub- including Latin & Thai (additional international characters available)
Bar Codes Linear 2D symbologies	Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-1 Interleaved 2 of 5, MSI/Plessey, UCC/EAN-128, UPC-4 UPC-E AZTEC, PDF417, QR
Graphics	Supports storage of graphics/logos in Flash memory at transient "print once" graphics
Software	
Protocol	Line Printer Mode, Easy Print®
Device Management	O'Neil Printer Management Console (OPMC), Wavelink Avalanche
Drivers	Windows CE and Desktop
Label Designers	NiceLabel, BarTender®, DP Designer
Agency Approvals	
FCC B, CE, UL/cUL, CB Schem	ne

* When used with approved media grades.
** Contact Technical Support for more information.

2 years (including printer case and printhead*)

Specifications are subject to change without notice.

PrintPAD** and Easy Print* are trademarks of O'Neil Product Development, Inc. All other product and company names are trademarks, service marks or registered trademarks of their respective owners.

Copyright 2009, O'Neil Product Development, Inc. rev. 02/09 Made in the U.S.A.

World Headquarters

O'Neil Product Development 8 Mason, Irvine, CA 92618-2705 Ph: 949.458.0500

Fx: 949.458.0708

email: info@oneilprinters.com



WWW.ONEILPRINTERS.COM